

## 65E | Motor Grader



# Compact Grader With Big Grader Features

- 53" Circle With "A" Frame Drawbar
- Full Power Shift Transmission With Torque Converter
  - Torque Proportioning Rear Differential

### 65E | Motor Grader



### **BIG GRADER FEATURES IN A SMALL PACKAGE**

### **Operating Weight**

Front 4,700 lbs
 Rear 12,200 lbs
 Total 16,900 lbs

### **Engine**

Cummins QSF3.8 Caterpillar C3.4
4 Cycle, turbo diesel
4 cylinder 4 cylinder
Tier 4 Final Tier 4 Final
120 hp 120 hp

### **Brakes**

- Power brakes
- Service 4 wheel, wet disc & self adjusting
- · Independent tandem by tandem system
- · Mechanical parking brake

### Axles

- Front axle clearance 20.3"
- Rear axle torque proportioning differential

### Transmission

- Full power shift with torque converter
- 6 speeds forward top speed 24 mph
- · Electronic shift control
- · LCD operations monitor
- · Shift inhibit system

### Circle

- 53" diameter gear driven circle
- Supported by "A" frame
- · 4 guides with wear plates
- Shim adjustable
- 360° rotation
- · Hydraulic circle side shift

### Moldboard

- "Rollaway" blade with involute curve
- · Replaceable cutting edges
- Size 10' wide, 21" high
- · Interchangeable end bits



Full power shift transmission with torque converter



53" gear driven circle with "A" frame allows 360° blade rotation




Illustration includes optional equipment

### **STANDARD EQUIPMENT**

- · Accelerator/decelerator and hand throttle
- Alternator 120 Amp.
- · Articulated frame
- Back-up alarm
- Battery 12 volt
- Controls, hydraulic
- Articulation
- Circle side shift
- Circle turn
- Moldboard lift/lower
- Moldboard side shift
- Wheel lean
- · Control console, adjustable
- Drawbar
- Engine side panels
- Gauges
- Air cleaner service indicator
- Engine coolant temperature
- Engine oil pressure
- Fuel and DEF level– Hourmeter
- Tachometer
- Transmission LCD message center
- $\\ Transmission \\ oil \\ temperature$

NOR/AM

– Voltmeter

- Horn, electric
- Hydraulic valve 8 section
- · Implement control lever lock
- Light package
  - Front headlights (2) hi/lo beam
- Front worklights (2)
- Turn signals, stop and tail lights
- Master electrical switch
- · Mechanical parking brake
- Muffler, horizontal under hood
- Moldboard 10' wide
- · Moldboard pitch, manual
- ROPS Canopy with
- Dome light
- $\, Floormat$
- Glove box
- Grab handles
- Headliner
- Inside mirrorSeat belt
- Seat, vinyl deluxe air suspension
- · Steps, right and left
- Tires 15.00 x 19.5 (8PR) G2 tubeless
- Transport tie down group
- · Vandalism protection



The information contained in this brochure is intended to be of general nature only. The manufacturer may at any time and from time to time, for technical or other necessary reasons, modify any of the details or specifications of the product described in this brochure. Illustrations do not necessarily show products in standard condition. The dimensions, weights and capacities shown herein, as well as any conversion data used, are approximate only and are subject to variations within normal manufacturing techniques. To be sure of getting accurate, detailed and up-to-date information, any intending buyer should contact NorAm.



- · Cab, includes
- Cloth seat air suspension
- Defroster fans (2)
- F & R wipers/washers
- Heater, 40,000 BTU
- Inside mirror
- Sliding rear window
- Sound suppression
- Tinted glass
- Dozer 8' x 2', with skid plates
- Engine block heater

- · Factory air conditioner
- Float control valves, (3)Floodlights, (2) F & (2) R
- Mirrors, rearview external, (2)
- Moldboard 12' wide
- · Moldboard pitch, hydraulic
- · Radio group
- Rear ripper 75" wide, 3 shanks
- Scarifier 41" wide, 9 teeth
- Strobe light
- 90° bank slope saddle



Deluxe cab



Scarifier



Dozer blade 90° Bank slope saddle